DRH81600R

DDR3-1600, PC3-12800, Registered, ECC, 1.5V, 240-pin DIMMs

Products in Family

DRH81600RS/4GB (1 x 4GB 1Rx4 DIMM)
DRH81600RS/8GB (1 x 8GB 1Rx4 DIMM)
DRH81600R/16GB (1 x 16GB 2Rx4 DIMM)

Features	Description
240-pin JEDEC-compliant DIMMs 133.35 mm wide by 30 mm high (1.181” x 5.25”) Data Transfer Rate: 12.8 Gigabytes/sec Operating Voltage: 1.5 V ±0.075 Fully RoHS Compliant Thermal Sensor HP SmartMemory compliant	Each DRH81600R upgrade consists of a single DDR3-1600 Registered ECC DIMM that conforms to JEDEC’s DDR3, PC3-12800 standard. One 2K-bit EEPROM is used for Serial Presence Detect and a combination register/PLL with Address and Command Parity is also used. A thermal sensor accurately monitors the DIMM module and can prevent exceeding the maximum operating temperature of 95C.

Dataram Product	HP Product	Supported in these HP systems:
DRH81600RS/4GB DRH81600RS/8GB DRH81600R/16GB	647895-B21 647899-B21 672631-B21	HP ProLiant BL460c G8, DL160 G8, DL360p G8, DL380p G8, ML350p G8, SL230s G8, SL250s G8

Front view



Notes

Tolerances on all dimensions except where otherwise indicated are ±.13 (.005).

All dimensions are expressed in millimeters [inches]

Back view



Side view



Copyright © 2012 Dataram Corporation | U.S.A. Headquarters +1 609-799-0071 | Offices in Europe and Asia | www.dataram.com

The information contained in this document has been carefully checked and is believed to be reliable and accurate. However, Dataram assumes no responsibility for errors.